

บริษัท อุดมโลหะกิจ (1975) จำกัด

และ

บริษัท ยู เอ็ม ที สตีล จำกัด



ตะแกรงเหล็กยัด

(EXPANDED METAL SHEET)



รุ่น	ช่องว่างของรู	ช่องยาวของรู	ความหนา	ลึน	4' x 8'
(CODE)	(SW)	(LW)	(T)	(W)	กก./แผ่น
XS : 31	12 mm.	30.5 mm.	1.2 mm.	1.5 mm.	7.01
XS : 32	12 mm.	30.5 mm.	1.6 mm.	2.0 mm.	12.05
XS : 33	12 mm.	30.5 mm.	2.3 mm.	3.0 mm.	26.80
XS : 41	22 mm.	50.8 mm.	1.6 mm.	2.0 mm.	6.78
XS : 42	22 mm.	50.8 mm.	2.3 mm.	2.5 mm.	12.20
XS : 43	22 mm.	50.8 mm.	3.2 mm.	3.5 mm.	23.80
XS : 51	25 mm.	61.0 mm.	1.6 mm.	2.5 mm.	7.46
XS : 52	25 mm.	61.0 mm.	2.3 mm.	3.0 mm.	12.90
XS : 53	25 mm.	61.0 mm.	3.2 mm.	4.0 mm.	23.90
XS : 61	34 mm.	76.2 mm.	2.3 mm.	3.0 mm.	9.48
XS : 62	34 mm.	76.2 mm.	3.2 mm.	4.0 mm.	17.60
XS : 63	34 mm.	76.2 mm.	4.5 mm.	5.0 mm.	30.90
XS : 71	50 mm.	152.4 mm.	2.3 mm.	3.5 mm.	7.52
XS : 72	50 mm.	152.4 mm.	3.2 mm.	4.0 mm.	11.92
XS : 73	50 mm.	152.4 mm.	4.5 mm.	5.0 mm.	21.00
XG : 11	34 mm.	135.4 mm.	4.5 mm.	7.0 mm.	43.10
XG : 12	34 mm.	135.4 mm.	6.0 mm.	7.0 mm.	57.70
XG : 13	34 mm.	135.4 mm.	6.0 mm.	9.0 mm.	74.00
XG : 21	36 mm.	101.6 mm.	4.5 mm.	7.0 mm.	40.70
XG : 22	36 mm.	101.6 mm.	6.0 mm.	7.0 mm.	54.40
XG : 23	36 mm.	101.6 mm.	6.0 mm.	9.0 mm.	70.10
XG : 15	25 mm.	125 mm.	4.5 mm.	7.0 mm.	60.10
S : 4	40 mm.	101.6 mm.	4.5 mm.	6.0 mm.	30.90
XS : 64	34 mm.	76.2 mm.	6.0 mm.	7.0mm.	49.00

รุ่น	ช่องว่างของรู	ช่องยาวของรู	ความหนา	ลึน	5' x 10'
(CODE)	(SW)	(LW)	(T)	(W)	กก./แผ่น
XS : 52	25 mm.	61.0 mm.	2.3 mm.	3.0 mm.	20.11
XS : 53	25 mm.	61.0 mm.	3.2 mm.	4.0 mm.	37.39
XS : 62	34 mm.	76.2 mm.	3.2 mm.	4.0 mm.	27.45
XS : 63	34 mm.	76.2 mm.	4.5 mm.	5.0 mm.	48.31
XS : 72	50 mm.	152.4 mm.	3.2 mm.	4.0 mm.	18.67
XG : 21	36 mm.	101.6 mm.	4.5 mm.	7.0 mm.	63.60
XG : 22	36 mm.	101.6 mm.	6.0 mm.	7.0 mm.	85.00
XG : 23	36 mm.	101.6 mm.	6.0 mm.	9.0 mm.	110.00





