

CONVERSATION LATHE



SPECIFICATIONS

ITEM 項目	Model 機種	CS-17 (430 mm)	CS-19 (470 mm)	CS-21 (520 mm)
Swing Over bed	床面上最大旋徑	430 mm (17")	470 mm (18-1/2")	520 mm (20-1/2")
Swing Over Cross Slide	橫送台上最大旋徑	240 mm (9-1/2")	280 mm (11")	330 mm (13")
Center distance (mm)	兩心間距離 (mm)	1000, 1500, 2200		
Width of Bed	床面寬度	300mm		
Spindle Nose	主軸鼻端	A1-6, D1-6 / A1-8 (OPT.) (選配), D1-8 (OPT.) (選配)		
Spindle bore	主軸孔徑	58 mm / 80 mm (OPT.) (選配)		
Taper of Spindle Bore	主軸通孔錐度	MT6 / MT7 (OPT.) (選配)		
Spindle Speed	主軸轉速	L: 20~180 rpm, H: 181~2000 rpm		
Control way of Spindle	主軸控制方法	Inverter Transmission 變頻控制		
Tail Spindle diameter	尾座心軸直徑	58 mm	68 mm	
Tail Spindle Travel	尾座心軸行程	150 mm		
Taper of Tail Center	尾座心軸錐度	MT 4		
Auto Feed range of X Axis	X軸自動進給速率	5 M/ min		
Auto Feed range of Z Axis	Z軸自動進給速率	10 M/ min		
Ball Screw of X Axis	X軸滾珠螺桿規格	ø 20 P5		
Ball Screw of Z Axis	Z軸滾珠螺桿規格	ø 38 P10		
Travel of X Axis	X軸移動距離	250 mm		275 mm
Travel of Z Axis	Z軸移動距離	900 mm	1400 mm	2110 mm
Main Drive Motor	主軸馬達規格	7.5 HP(5.5KW) / 10HP (7.5 KW) (OPT.)(選配)		
Machine dimensions (cm)	佔地面積			
	長 (cm)	L : 245 / 295 / 375	L : 245 / 295 / 375	L : 245 / 295 / 375
	寬 (cm)	W:170	W:170	W:170
	高 (cm)	H:167	H:167	H:167
Net Weight (Kgs)	淨重 (公斤)	1760, 2050, 2405	1800, 2075, 2465	1810, 2135, 2565